MicroSurvey STAR*NET 8

Features and Benefits

Brian Sloman

STAR*NET 8: Features & Benefits

Table of Contents

STAR*NET 8
CS-Map Coordinate System Engine2
Geoid Modeling (.bin/.byn files)
STAR*NET 8.1
Network Plot4
.PRISM Command5
Google Maps™ Support6
Google Earth™ Support7
Level Loop Tolerance Check
Online Updater9
File References10
Data File Monitor
STAR*FieldGenius Enhancements12
STAR*Carlson Enhancements12
STAR*Leica DBX Enhancements13
Miscellaneous Enhancements13
STAR*NET 8.2
Adjust Network with Cluster Detection14
Adjusted Observations and Residuals15
Adjustment Speed Improvement15
Select Ellipsoid16
Data Conversion and GPS Vector Import Improvements17

STAR*NET 8

Release Date: May 9, 2014

CS-Map Coordinate System Engine

🔀 MicroSurvey STAR*NET-DEMO - Tutorial09-VectorCom	bined	
File Edit Options Input Run Output Tools		
i 🖗 🖺 😂 🖬 🐚 l 🖨 🔍 🕗 🧯 🗠 🖄 🗘 i		
Data Input Files 🔹 🗸 🗸	Tuto Project Options	→ # ×
2 T 🖻 T 🕆 D D 🔺 🔻 👘	1 Adjustment General Instrument Listing File Other Files Special GPS Modeling	
Index Tutorial09-VectorCombined U Index In	Adjustment Type 2 2 3 4 2 2 2 4 2 2 2 2 2 2 2 2 2 2 2 2 2	MicroSurvey STAR*NET-DEMO Ver + Licensed for Demo Us Run Date: Wed Jul 09 201
Processing Summary 👻 🖡 🗙	9 3D 9 Ceveling Select Project Coordinate System	Summary of Files Used and Op
	Coordinate System Group: State Planes, NAD83	Project Folder and Dat roject Name TUTORIAL09-VECTORCOMBI
	14 ● Grid: 15 Average Coordinate System: AZ83-C ▼ tom System	roject Folder C:\USERS\\DOCUMENTS ata File List 1. Tutorial09-VectorCombi 2. Tutorial08-VectorJob.g
	17 Zone, Meter 18 O Local Datum: North American Datum of 1983	Project Option Sett
	19 Datum St Committee 20 (@ Apply 1 Ellipsoid: Geodetic Reference System of 1980 21 (@ Reduit Reduit Geodetic Reference System of 1980	TAR*NET Run Mode : Adj ype of Adjustment : 3D roject Units : Met
Network Plot → ↓ ×	23 24 Geoid/Vertica OK Cancel Help	oordinate System : AZ8 eoid Height : -31 ongitude Sign Convention : Pos
	25 Using Geold Modeling 26 Using Vertical Deflections 27	nput/Output Coordinate Order : Nor ngle Data Station Order : At- istance/Vertical Data Type : Slo
	28 To change these options please refer to the Modeling Tab 29 30 31	Listings / Errors / Coordnates / Lat/Longs / Ground / Dum
Find	Point OK Cancel Help	
N: 220357.7 E: 138349.3 Width: 24509.28 Ready		CAP NUM SCRL
ready		CAP NOM SCRE

Feature	Benefit
CS-Map coordinate system engine	100% cross-compatibility between all MicroSurvey products including STAR*NET, FieldGenius, MSCAD, inCAD, embeddedCAD, etc.
Over 3800 predefined coordinate systems, worldwide, are now available to select from	Greatly expands the usability of STAR*NET especially outside of North America, as only UTM and SPCS zones were previously available.
Custom Coordinate System Editor supports more datum and projection types	The old text-based coordinate system definition file "starnet.cus" was very limited in the systems that could be defined because it only supported a few projection types.

Geoid Modeling (.bin/.byn files)

MicroSurvey STAR*NET-PRO - Tutorial04-Grid3D		
File Edit Options Input Run Output Tools View		
] 🚳 🖺 📂 📾 🐚 🖨 🔍 🕢 🦕 🕍 🖄 🗗 🚱 🦛 Data Input Files	Project Options	<u>+</u> û ×
Index Index <t< td=""><td>Adjustment General Instrument Listing File Other Files Special GPS Modeling Models Folder: C.\ProgramData\MicroSurvey\StarNet\V8\Mapping Info Info</td><td>The MicroSurvey STAR*NET-PRO Version 8,1,2,5 A Run Date: Wed Jul 30 2014 17:06:30</td></t<>	Adjustment General Instrument Listing File Other Files Special GPS Modeling Models Folder: C.\ProgramData\MicroSurvey\StarNet\V8\Mapping Info Info	The MicroSurvey STAR*NET-PRO Version 8,1,2,5 A Run Date: Wed Jul 30 2014 17:06:30
	Perform Geoid Modeling	Summary of Files Used and Option Setting
Processing Summary * 0 × Zeniths 8 1.677 × Total 26 0.935 Chi-Square Test at 5.00% Level Pass	Automatic Selection from Geoid Files Select Specific Geoid File: g2009u05.bin Show Modeled Geoid Heights in Listing File Perform Vertical Deflection Modeling:	Project Folder and Data Files TUTORIAL04-GRID3D C:\USERS\\DOCUMENTS\MICROSURVE\ 1. Tutorial04-GRId3D.dat
Lower/Upper Bounds (0.589/1.412) Performing Error Propagation Writing Output Files	Select Specific Deflection Files Select Specific Deflection File: Show Modeled Vertical Deflections in Listing File	T I. Iutorialus-oriasu.dat Project Option Settings Mode : Adjust with Er: tment : 3D
Network Processing Completed Elapsed Time = 00:00:00	Apply Constant Deflections Only: N=	stem : FeetUS; DMS stem : CA83-III Model : C:\PROGRAMDATA n Convention : Fositive West Coordinate Order : North-East
		Action Order : At-From-To ical Data Type : At-From-To ical Data Type : Slope/Zenith imit; Max Iterations : 0.010000; 10 icient of Refraction : 0.070000 nate File : Yes ic Position File : Yes
A2 A4 cas	OK Cancel Help	- # X
N: 2191383.4 E: 6419917.3 Width: 9707.17 Feet		
Ready		CAP NUM SCRL


Feature	Benefit
Direct support of NGS and NRCan geoid files (.bin/.byn) for geoid modeling	Conversion to .ght format (using the STAR*Geoid utility) is no longer necessary. This improves user confidence by using officially distributed geoid files from NGS/NRCan. Further, STAR*Geoid did not support NRCan's newer .byn format (like HT2_0.byn).
Hundreds of worldwide geoid models are available for download via the MicroSurvey Helpdesk.	Easy and free access to geoid models.

STAR*NET 8.1

Release Date: August 1, 2014

Network Plot

Upgrade Tour Movie: click here




Feature	Benefit
New Plot Options dialog	All network plot display options are now customizable (for example: no hard-coded colors) in an intuitive but powerful dialog.
Specify the color, size, and linetype of each network element	Graphically differentiate Conventional, GPS, and Leveling observations by color or linetype, etc. More control for the user.
Directional Linetypes	Directional arrowheads provide an immediate indication of both the direction and number of observations between two stations. Users can quickly notice regions with low redundancy without having to analyze the listing.
Zoom and Pan mouse controls	Intuitive CAD-like mouse control makes manipulating the network plot view fast and easy.

.PRISM Command

MicroSurvey STAR*NET-DEMO - Tutorial09-Vector	rCombined
File Edit Options Input Run Output Te	iols View Window Help
i 🖗 🖺 📂 🖬 🐚 🖨 🔍 🥹 🚽 🗠 🖄	ⓒ⑥Μ،،(****)○○○,↓ ≶ ⊠ 図 細 訂 .
Data Input Files 🚽 🗸 🗸	Tutorial09-VectorCombined.dat X Tutorial08-Vector/0b.gps Vulput
Index Index <t< td=""><td>1 # Combining Conventional Observations and GPS Vectors 2 # Latitudes and Longitudes are used as constraints in this 3 # The "VectoryDo.GPS" if le is added in the Data Files Dialo 4 Number of Measured Angle Observ 5 P 0012 33-04-44.24402 112-54-36.04569 224.299 ! ! ! North 6 P 0013 23-56-09.73117 112-47-13.55717 209.384 ! ! ! 'AZDOT 7 F. 0013 205.450 . ! 'BM-9331</td></t<>	1 # Combining Conventional Observations and GPS Vectors 2 # Latitudes and Longitudes are used as constraints in this 3 # The "VectoryDo.GPS" if le is added in the Data Files Dialo 4 Number of Measured Angle Observ 5 P 0012 33-04-44.24402 112-54-36.04569 224.299 ! ! ! North 6 P 0013 23-56-09.73117 112-47-13.55717 209.384 ! ! ! 'AZDOT 7 F. 0013 205.450 . ! 'BM-9331
Processing Summary # 0 × 2 × 0 × 1 × × × × × × × × × × × × × × × × × ×	F 0013 205.450 1 FBM-9331 0051 0013 0052 160-18-01.70 8 0051 0013 0052 160-18-01.70 9 TB 0012 0052 0051 0013 0052 121-47-22.10 10 .FRISM 30 0051 0013 0015 240-35-47.03 12 T 0051 160-18-01.7 2208.27 90-14-33 5.40/5.40 0052 0051 0013 0015 240-35-47.03 13 .FRISM CLEAR 0052 0051 0016 142-02-01.50 14 T 0052 123-47-22.1 2202.07 89-43-20 5.36/5.40 'SW Bru 0053 0052 0016 142-02-01.50
Lower/Upper Bounds (0.719/1.2 Performing Error Propagation Writing Output Files	15 T 0053 198-52-17.3 2714.30 89-58-19 5.35/5.38 Number of Measured Distance Observ 16 TE 0013 To Distance StdErr 0013 0051 4013.9800 0.0158 5.35
Network Processing Completed Elapsed Time = 00:00:00	13 14101 0051 0051 0051 0052 2208.300 0.0122 5. 20 M 0051-0013-0015 240-35-47.03 1601.22 90-27-52 5.40/5.4 0051 0052 2208.300 0.0122 5. 21 .FRISM CLEAR 0052-0051-0015 320-50-46.25 2499.61 90-05-49 5.36/5.4 0053 0018 2714.3000 0.0122 5. 23 M 0052-0051-0016 142-02-01.50 2639.68 90-07-37 5.36/5.4 0051 0015 1601.2500 0.0111 5. 24 M 0053-0052-0016 61-14-43.77 2859.65 90-20-19 5.35/5.4 0052 0016 2639.6800 0.0131 5.
२, २, थे, २, + ⊕ ि" & । । । । । । ।	26 0053 0016 2859.6500 0.0135 5. Number of Zenith Observatio From To Zenith StdErr
an te	Image: Contract of the second seco
V: 220357.7 E: 138349.3 Width: 24509.28	
Ready	CAP, NUM, SCR


Feature	Benefit
Specify an prism offset correction to add to all following distances	Very easy to correct a fairly common field mistake: using a prism with the wrong prism offset setting. Previous solution required calculating and hand- modifying every incorrect distance value (potentially thousands of manual edits), which is time consuming and very prone to error. This will absolutely save users time and money!
.PRISM value	You can specify one offset value (in millimeters), and STAR*NET will scale it to the appropriate unit and add it to the distance values that follow.
.PRISM value1 value2	You can specify two offset values (both in millimeters), and STAR*NET will subtract them (value1-value2), scale the difference to the appropriate unit and add it to the distance values that follow. This allows you to specify the correct prism offset value and the incorrect prism offset value that was used for the measurements, rather than just a correction value.
.PRISM OFF ON CLEAR	Stop, start, and reset the prism correction. If the mistake was realized and corrected halfway through the survey, just add a .PRISM OFF or .PRISM CLEAR command after the last incorrect observation to stop applying the correction value.

Google Maps[™] Support



Feature	Benefit
View Point in Google Maps	Users can view their adjusted network stations
	(2D/3D Grid projects only) in a free online service
	that everyone is already familiar with.

Google Earth™ Support



Feature	Benefit
View Network in Google Earth	Users can view their adjusted network stations and connections (2D/3D Grid projects only) in a free* program that everyone is already familiar with.
Export .kml/.kmz File	The .kml or .kmz file is another deliverable that our users can provide as a value-add to their clients.

Level Loop Tolerance Check

Upgrade Tour Movie: click here

	Project Options	× -	Output					▼ -
	Adjustment General Instrument Listing File Other Files Special GPS Modeling	*nc _	14 <4 4		⊑ Differential Lev			
Tuto	Postional Tolerance Checking		Tolerance		ard: NGS, Second			
	Tolerance: 0.10000 FeetUS Confidence: 95,000 %	.93	From	То	Elev Diff	StdErr	Length	File:Line
essing etworl	0.000 PPM		128 130	130 129	10.3360	0.0148	32100 37400	1:16
ading	List: Tolerance Failures Only All Connections	=	130 129 Error of	128	-22.1300 11.8100 -0.0160	0.0160 0.0169	37400 41700 111200	1:13 1:15
op Cl	Check Sideshots	ira Iyc	Error of Standard	Closure Tole Error:	rance: ±0.1606 0 0.0275	DK		
apsed	For Network Matches: For Repeated SS Names: (a) No Checking (b) No Checking		130	zed Error: 125	0.5811 3.8330	0.0138	28100	1:14
	Issue Warning Message Issue Warning Message Issue Error Message Issue Error Message		125 BM75	BM75 129	-15.9200 -10.0230	0.0146 0.0131	31200 25300	1:12 1:11
	Level Loop Check		129 Error of		22.1300 -0.0200 rance: ±0.1682 0	0.0160	37400 122000	1:13
vork Pic	Level Loop Creck	in	Standard		0.0288			
	NGS ▼ Second Order Class II ▼ 0.035 ft √M		128 126	126 130	34.4220 -24.0650	0.0189	52200 40900	1:20 1:19
			130 Error of	128 Closure:	-10.3360 -0.0210	0.0148	32100 125200	1:16
		•			Coordinates / Lat/Long	s / Ground / I	Dump /	
	OK Cancel	Help						

Feature	Benefit
Loop Lengths given in Listing	Analysis of listing file is easier/faster because all relevant information is displayed together in the same section. No need to jump back and forth between different sections to determine the segment lengths, and no need to manually sum
	them to compute the total loop lengths.
Tolerance Check (optional)	Automatically analyze whether differential leveling loops meet specific classification requirements. Written with pre-configured standards of accuracy from United States National Geodetic Survey and Natural Resources Canada, but it also allows for using a custom classification formula.

Online Updater

MicroSurvey STAR*NET-DEMO - Tutorial09-VectorCombined		
File Edit Options Input Run Output Tools View Win	Jow Help	
i 🖗 🖺 📂 🗔 🐚 🖨 🔍 🕢 💭 🕾 🖉 🕼 😭 🛽) () () () () > 2 2 2 10 fr .	
Data Input Files 🛛 🗸 🗸 🗸 Tutoria109-V	ectorCombined.dat Tutorial08-VectorJob.gps 🗙 💌 Output	→ # ×
	WEIGHT COVARIANCE	► ► TE
Tutorial09-VectorCombined G1 0 Tutorial09-VectorCombined G2 Tutorial09-VectorCombined G2	Comparison of the second	MicroSurvey STAR*NET-DEMO Ver - Licensed for Demo Us Run Date: Wed Jul 09 201
Processing Summary 9 G1 0	vz Choose Updates to Install	Summary of Files Used and Op
11 G3	3. 4. Updates	Project Folder and Dat
	1. Manager).	Name TUTORIAL09-VECTORCOMBI Folder C:\USER\$\\DOCUMENTS e List 1. Tutorial09-VectorCombi 2. Tutorial09-VectorZob.g Project Option Sett Run Mode : Adj Adjustment : 3D Units : Met te System : AZ8 ight :-31 e Sign Convention : Pos tput Coordinate Order : Nor ta Station Order : At- /Vertical Data Type : Slo nce Limit; Max Iterations : 0.0 Coefficient of Refraction : 0.0
Find Point	Net Cancel	Errors / Coordinates / Lat/Longs / Ground / Dum
N: 234272.0 E: 124106.3 Width: 24509.28		
Ready		

Feature	Benefit
Check For Updates	Users can quickly check online to see if there are any updates available to download and install. This makes it easy for users to ensure they are using the latest version so they can get the most out of their maintenance subscription and support plan and maximize their return on investment.
Auto Update	Users can be informed automatically, without having to do a check. Again, this helps users maximize their ROI.
Auto Update Preferences	Users can change the automatic update check frequency, or disable it completely if they do not intend on renewing their maintenance in order to continue getting the latest updates.

File References

					0.1						
Data Input Files			ial09-VectorCombi 🗙 🔻	Output							-
] 🖬 🖬 🛱 🛱 🖻 🖷 🖉 💎 👘		1	# Combining Co	14 - 44 -	() () ()	[E=					
	Index	2	<pre># Latitudes an # The "VectorJ</pre>				Observations and				
Tutorial09-VectorCombined		4	# THE VECCOID								
Tutorial09-VectorCombined.dat	1	5	P 0012 33-04- P 0017 32-58-			Adjusted Me	asured Angle Obser	rvations (DMS)			
		7	E 0013 205.45	At	From	То	Angle	Residual	StdErr	StdRes	File:Line
ocessing Summary	▼ # ×	8	TB 0012	0013	0012	0051	67-58-22.13	-0-00-01.37	0.52	2.6	1:10
Network Adjustment with Err		10	TB 0012 T 0013 67-5	0051	0013	0052	160-18-02.35	0-00-00.65	0.61	1.1	1:11
ACCWOIR AUJUSCHEITE WICH EIT		10	T 0013 67-5	0052	0051	0053	213-47-21.90	-0-00-00.20	0.67	0.3	1:12
Loading Network Data		12	T 0051 160-1 T 0052 213-4	0053	0052	0018	198-52-17.29	-0-00-00.01	0.65	0.0	1:13
Checking Network Data		13	T 0053 198-5	0051	0013	0015	240-35-46.47	-0-00-00.56	0.66	0.9	1:17
onconing account baba		14	TE 0018	0052	0051	0015	320-50-47.48	0-00-01.23	0.57	2.2	1:18
Performing Network Adjustme	nt	15	IE 0018	0052	0051	0016	142-02-01.73	0-00-00.23	0.64	0.4	1:19
Iteration # 1		16	# Ties to GPS	0053	0052	0016	61-14-43.58	-0-00-00.19	0.58	0.3	1:20
Iteration # 2			M 0051-0013-00								
Iteration # 3			M 0052-0051-00		Ad	justed Measu	red Distance Obser	vations (Meter	rs)		
Solution Has Converged in 3	Iterati		M 0052-0051-00								
-			M 0053-0052-00		From	To	Distance	Residual			File:Line
Statistical Summary		21			0013	0051	4013.9490	-0.0010	0.0158		1:10
Observation Count Err	or Factor	22	L 0013-0017 3.		0051	0052	2208.2595	-0.0105	0.0122		1:11
Angles 8	1.834				0052	0053	2202.0798		0.0122		1:12
Distances 8	1.208				0053	0018	2714.3235	0.0235	0.0132	1.8	1:13
Zeniths 8	1.226				0051	0015	1601.2156	-0.0044	0.0111	0.4	1:17
Level Data 1	0.000				0052	0015	2499.6096	-0.0004	0.0128	0.0	1:18
GPS Deltas 24	0.688				0052	0016	2639.6911	0.0111	0.0131	0.8	1:19
Total 49	1.125				0053	0016	2859.6601	0.0101	0.0135	0.7	1:20
Chi-Square Test at 5.00% Le	Tral Page					Adjuste	d Zenith Observati	ions (DMS)			
Lower/Upper Bounds (0.724			~	•							
LINE, IPPIL Dounds (01/11	,	< Ⅲ	►		Listings / Error		Lat/Longs / Ground / D	ump /			
Performing Error Propagatio	n	ind Point					/			_	
Writing Output Files		ina Point									

Feature	Benefit
Index column in Data Input Files panel	File References (like 1:10 for File 1, Line 10) correspond to the new Index shown beside each data file. For projects containing many data files,
	this makes it easy to identify the appropriate file.
Double-click File:Line in Listing	Double-clicking on a : character (like in 1:10) immediately jumps to the appropriate file and highlights the appropriate line.

Data File Monitor

K MicroSurvey STAR*NET-DEMO - Tutorial09-VectorCombined	
File Edit Options Input Run Output Tools View Window Help	
i 🖗 🗅 😂 🖬 🐚 🖨 🔍 🕗 ji 🗠 ta K. O. G. M. 🕐 Ů ČI ČI K. ji 🗲 🛛 🛛 🖓 👘 🚦	
Data Input Files • 4 × Tutorial09-VectorCombined.dat x Tutorial08-VectorJob.gps	▼ Output
<pre></pre>	MicroSurvey STAR*NET - Licensed fo Run Date: Tue J Summary of Files Us Project Folde Project Folde Project Name TUTORIAL09-VE Project Folder C:\USERS\\ Data File List 1. Tutorial09-VE 2. Tutorial08-VE Project Op STAR*NET Run Mode Type of Adjustment Project Units Coordinate System Geoid Height Longitude Sign Convention Input/Output Coordinate Order Angle Data Station Order Distance/Vertical Data Type Convergence Limit; Max Iteration Default Coefficient of Refractio . * * * * * * Listings / Errors / Coordinates (LatLongs / Converted)
N: 227357.2 E: 138475.8 Width: 24509.28 Ready	CAP NUM SCRL
······································	CAP NOM SCRE

Feature	Benefit
Data editor will automatically refresh any open data files that are overwritten or appended to by the GPS Import command	Previously, users had to close and reopen the data file in order to refresh the file – this could result in confusion with not seeing the new data, accidentally re-saving the old data and losing the new data, and other similar problems. The new refresh is instant and automatic.
Data editor will prompt to refresh any open data files that are modified outside of STAR*NET	 A data file might be modified outside of STAR*NET in several scenarios, like: The "Edit External" button is used to open up the data file in some other text editor Somebody on another computer is editing the file A file is updated by re-exporting it from one of the conversion utilities or other survey software The new behavior helps ensure that the editor always displays the expected data. It is automatic and intuitive, and STAR*NET now behaves like other modern text editors in this sense.

STAR*FieldGenius Enhancements

Upgrade Tour Movie: n/a

Feature	Benefit
Convert OB (Observation) records from the .raw file to BM (Bearing Measurement) records in the .dat or .gps data file	Some users handled point offsets by performing a COGO calculation to create a new point relative to another measured point. These calculations now carry over into the converted STAR*NET data.
Convert GO (GPS Offset) records from the .raw file to G4 records in the .gps data file	GPS Offset measurements, when imported to STAR*NET, used to ignore the offset and create the resulting point at the measured position instead of offsetting it as specified. The offset is now imported to the new "G4" record. This defines the offset direction and distance, resulting in the "to" point being created in the correctly offset position.
New G4 Data Record can be added to any vector group in a STAR*NET data file (not just FieldGenius)	The new G4 records are currently only created by the FieldGenius GPS importer, but it is a generic solution that can be manually added to any vector, and in the future we can add this to other GPS import formats as necessary.
Fixed other issues importing FieldGenius GPS data	Overall robustness has been improved by fixing problems with various "odd" scenarios that have been reported.

STAR*Carlson Enhancements

Upgrade Tour Movie: n/a

Feature	Benefit
Import Resection Observations	Resections used to be ignored, so you lost some potentially important observation data. It now creates Direction Set with a DM record for every shot.
Average Shots in Multiple Sets (option)	This is an option that Starplus removed from STAR*Carlson several years ago, and SurvCE users asked us to bring it back. If you do a Set (say, backsighting point 1 and foresighting point 2), then do another, and another, etc the Converter will average the sets together and write a reduced observation.
Import GPS Descriptions (option)	The option to Import Descriptions did not work, now it does. Self-explanatory.

STAR*Leica DBX Enhancements

Upgrade Tour Movie: n/a

Feature	Benefit
Use All Set Observations (option)	This option, added in 8.0, only applied to sets collected with the "Sets of Angles" application; it now also applies to sets collected with the "Traverse" application.
DMS Angular Precision (option)	The Angular Precision setting now controls the number of decimal places for the seconds value (like 2 for DDD-MM-SS.ss) instead of the degrees value (like 6 for DDD-MM-SS.ss). This is more intuitive.
Staking Observations (option)	Staking observations can now be converted as Measurement records.
Checkshot Deltas	Checkshot deltas will now be converted as comment records.

Miscellaneous Enhancements

Upgrade Tour Movie: n/a


Feature	Benefit
Project Manager, Template Data File (option)	In STAR*NET 6 new projects were always created with a blank data file. In STAR*NET 7 we added a template mechanism, and new projects were always created with a copy of that template data file. Most users didn't take advantage of the ability to customize the template file (for example by adding their commonly used control points, etc) so in STAR*NET 8.1 we added an option
Listing Index Tree	When using the Listing Index Tree, clicking on a section may jump the selected heading to the bottom of the Listing view. This was probably the #1 bug report since STAR*NET 7.
2D DXF Files	When exporting a DXF file, a defect with the option to "Export as 2D DXF File" has been fixed. This was a very common bug report.
Custom Coordinate System Editor	Several issues present in STAR*NET 8.0 have been fixed, making the Custom Coordinate System Editor easier to use and more flexible in 8.1. For example, custom systems can now be edited or deleted.

STAR*NET 8.2

Release Date: July 29, 2016

Adjust Network with Cluster Detection

Upgrade Tour Movie: click here



Feature	Benefit
Run > Adjust Network with Cluster Detection	New adjustment method that automatically detects multiple points with different IDs that are within a specified 2D or 3D proximity of each other and treat them as one point during the adjustment. A dual-pass adjustment will be performed, whereby a complete adjustment will first be run with all iterations, then its results analyzed to determine which points to combine, and a second adjustment will be run with those points aliased together.
Cluster Detection Dialog	After the first adjustment, you will have full control to approve or override any aliasing decisions prior to running the second adjustment, including the ability to control which point ID to use for each cluster.
Special Options	Specify a 2D or 3D distance tolerance, and choose whether or not to include or exclude points that are beyond tolerance of the true point in the cluster but within tolerance of any other point(s) in the cluster.
Listing Options	After the final adjustment, the listing file will report which points were aliased together in each cluster and will display their deltas from the true point.

Adjusted Observations and Residuals

Upgrade Tour Movie: <u>click here</u>

nduffer - • • × / 약 해 한 한 한 환 환 소 호		verse Grid Job		14 - 44		Tr=					_
A second the second of the second of the second	3 C A1 21	86970.930 6417594.370 300.00 1 1 1				1.000					
Tutorial04-Grid3D	4 C A2 21	86836.940 6415494.520 298.89 ! ! !				ervations and					
a Tutonal04-Grid 3D ✓	5 6 #PH A1 7 #PH A2	38-00-00.000012 120-59-59.899970	195.013 /// 8 903 ///		Adjusted Measur						
	9 TB A2 #	- Top of File		At Fro		Angle	Residual	Distance			File:Line
sing Summary 👻 🛛 🗙	10 T A1 1	1 Im Summary of Hies Used and Option Settings		A1 A2 1 A1		163-59-26.03	0-00-00.03	0.0002		0.0	1:10
twork Adjustment with Error Propagation	11 T 1 1 12 T 2	E Summary of Unadjusted Input Observations		1 A1 2 1	2		-0-00-00.08	-0.0004	2.61		1:11
	12 1 2 13 T 3	Adjustment Statistical Summary Adjusted Station Information		3 2	A1		-0-00-00.03	-0.0003		0.0	1:13
ading Network Data	14 TE A1	Adjusted Station Information Adjusted Observations and Residuals	0.1	A1 3	1	75-45-17.61		0.0000		0.0	1:14
ecking Network Data	15	Adjusted Measured Angle Observations		2 1		133-21-35.89	0-00-00.09	0.0012		0.0	1:17
rforming Network Adjustment	16 TB 1	- Adjusted Measured Distance Observations		4 2		101-39-39.56 124-35-19.49	-0-00-00.04	-0.0003		0.0	1:18
Iteration # 1	17 T 2 1 18 T 4 1	Adjusted Zenith Observations		A2 5	AL	80-48-52.16		-0.0009		0.0	1:20
teration # 2	19 T 5 1	Adjusted Bearings and Horizontal Distances Firaverse Closures of Unadjusted Observations		5 4	6	69-59-28.70		0.0000		0.0	1:22
lution Has Converged in 2 Iterations	20 TE A2	Firor Propagation End of File	n Al		Adjusted Measured	Distance Obse	rvations (Feet)	US)			
ervation Count Error Factor	22 M 5-4-6	- End of File									
Angles 10 0.050	23			Fro	m To	Distance 1153.6715	Residual 0.0015	StdErr StdR 0.0562 0.			
Distances 8 0.145				AL	2	1709.7838	0.0015	0.0590 0.			
Zeniths 8 1.922				2	3	1467.7375	-0.0025	0.0578 0.			
fotal 26 1.069				3	A1	2161.7661	0.0061	0.0612 0.			
i-Square Test at 5,00% Level Passed				2	4	2746.2858	0.0058	0.0641 0.			
Lower/Opper Bounds (0.522/1.480)				4	5	1396.7562	-0.0038	0.0574 0.			
forming Error Propagation				5	6	2045.2500	-0.0000	0.0606 0.			
iting Output Files					Adjusted Ze	nith Observat	ions (DMS)				
twork Processing Completed				Fro	m To	Zenith	Residual	Distance	StdErr	StdRes 1	File:Line
apsed Time = 00:00:00				Al	1	91-35-23.01		-0.0391		1.1	1:10
				1	2	90-56-31.48	-0-00-10.12	-0.0839	6.06		1:11
		C		23	3	90-08-49.72	-0-00-09.39	-0.0961			1:12
				2	4		-0-00-04.18	-0.0556			1:17
#				4	5	88-23-29.63	-0-00-02.17	-0.0147	6.09	0.4	1:18
nit Rat + 4 ×				5	A2		-0-00-05.53	-0.0978		0.9	1:19
(= ≪ = + # ₽ 🗞 😒				5	6		-0-00-00.00	-0.0000	6.04	0.0	1:22
				Adj	(Relative Confide						
				From To	Grid Bearin			-, Confidence			
(N)						Grnd Dist	Brg Di	at PPM			
				1 2	N05-55-29.21	1709.5533		992 58.0143			
				1 A1	\$70-20-22.30		5.48 0.0	939 81.4314			
(A)-A				2 3	N87-32-52.98			906 61.7420			
$\varphi \varphi$				2 4	N40-42-54.94	W 2744.9985	6.46 0.1	159 42.2044			
	•		1 3	I I H H Listings	<pre>/ Errors / Coordinates / Lat/</pre>	ongs / Ground / D	lump /				


Feature	Benefit
The Listing file now reports an effective distance value along with any angular residuals in the "Adjusted Observations and Residuals" section, including Angles, Zeniths, Directions.	This makes it easier to interpret the angular residuals without having to cross-reference it against the slope distance of the measurement. More easily identify possible issues like an incorrect target height.

Adjustment Speed Improvement

Upgrade Tour Movie: n/a

Feature	Benefit
A major slowdown when adjusting projects in	Network adjustments run much faster than
STAR*NET 8.0/8.1 has been fixed.	previous versions, saving time.

Select Ellipsoid



Feature	Benefit
Specify whether to use the local ellipsoid per the selected coordinate system or WGS84	 STAR*NET V6/V7 always used the local ellipsoid (for example: NAD27 systems use Clarke 1866 and NAD83 systems use GRS80), and STAR*NET 8.0/8.1 always used the WGS84 reference ellipsoid. STAR*NET 8.2 gives you the flexibility to choose depending on your needs. This affects all geodetic input and output values, including latitude/longitude positions and ellipsoid heights such as P/PH/CH/EH records, the Geodetic Position (.pos) file, and the Listing (.lst) file.

Data Conversion and GPS Vector Import Improvements

MicroSurvey STAR*NET-PRO - Tutoria/09-VectorComb File Edit Options Input Run Output Tools	View Window Help	
	🔍 😧 🖕 🗠 😒 🔏 🖆 👘 🏠 🏠 🖉	
🛛 🚏 🕅 🏷 🖻 🕅		Station Latitude Longitude Ellip Ht
Tutoria/05-Viecto/Combined Tutoria/05-Viecto/Combined dat Tutoria/05-Viectoriate gos Stars-LEICA Designed	8 G0 'V1 Day125(1) 14:116 00120 1 dex 6 G1 0012-0013-507.727807-57 5 G2 6.28935385644552E-008 2 6 G3 7.06118738719731E-008 -1 7	-5749, 39410 - 4 174-502 08-933 256-935 256-95 256-935 256-95
Oxford Date Re-	C:\www.fdbwid51025R1_8771_1082_162031/51005R1_8771_1 (c) Benne 1512025R1	Image: Provide and Data Product and Data Image: Provide And Data Prodata <
Geoid Path:	Browse	9169928450 Inport Vew Lag Heb Close
CSCS Path:	Browne	7.55F
Departung Summary Un Ontrove M Angular ()	atem 6 West Y Reach 0 India Al State in Sets VM est SY Reach 0 PS Conductes 0 PS Conductes 45 2 PS of Angles 0 PS Conductes 0 PS conductes V State S Select 0 PS Conductes PS conductes 0 PS conductes 0 PS conductes 0 PS conductes PS conduct	1.2935 -714 - 89439 93394 - 13300 -007 1.1394 77287. 93394 - 13300 -007 1.1394 77287. 945802402382 - 008 - 4.071 ± 57ArCARISON 9.57 945802402382 - 008 - 4.071 ± 57ArCARISON 9.57 945802402382 - 008 - 4.072 ± 57ArCARISON 9507 95179057738 - 008 - 4.723 ± 57ArCARISON 004 Dial File 014 Dial File <t< td=""></t<>
	atora de handere in Station Names te: tion Names Separator Grandere te: Color	C Cateria M Lans In Al Stations
		Heb Dow
4		

Feature	Benefit
Many improvements to several of the data conversion utilities and GPS vector importers	Improved compatibility with FieldGenius, Leica, Carlson, Trimble, TDS, and other data collectors.
Improved FieldGenius compatibility	Several improvements to support importing GPS vectors from MicroSurvey FieldGenius raw data files.
Improved Leica compatibility	Many improvements to support importing Sets of Angles data, Resection data, Reference Line data, Measure Foresight data, Survey data, append attribute data to your point codes, specify a NE or EN coordinate order, and more.
Improved Carlson compatibility	Various improvements to support importing resections and GPS vectors from Carlson raw files.
Improved Trimble compatibility	Various improvements to support importing Trimble JobXML (.jxl) and Trimble DiNi (.dat) files, and importing GPS vectors from Trimble TSC (.dc) files.
Improved TDS compatibility	Various improvements to support importing GPS vectors and leveling data from TDS raw (.rw5) files.
And much more	Please see the <u>STAR*NET 8.2 Release Notes</u> for a detailed list of all data conversion issues that have been resolved.